



MINGPOWERS

M-C163(6C) Technical Data sheet



**Professional Genset Manufacture On Your Side
Fujian Minghui Mech & Elec Co., Ltd.**

DIESEL GENERATOR

Powered by **Cummins** Engine & **Leroy somer** Alternator

STANDARD SPECIFICATION

Three phase four wire,output voltage 400V/230V,50HZ,between 0.8 lagging,protection capability according with the standard of NAME1 and IP23.

General Features:

Composed of **Cummins** diesel engine and **Leroy somer** alternator

Oil and fuel filter fitted,water separator

Lube-oil drain valve fitted

Electric Starter Charge motor 24 VD.C

Water-cooled

baseskid fuel tank

Auto start

Optional soundproof and weatherproof canopy

3 pole MCCB Delixi breaker/Optional ABB

ΔOperation & Maintenance manual

Special Integrated Steel Base tank and sprayed overall in gloss enamel paint



Voltage Regulation

Voltage regulation maintained within $\pm 0.5\%$

Between 0.8 and 1.0 lagging and unity

From no load to full load

At speed droop variation upto 4.5%

Frequency Adjustable Ratio

Change load from 0-100%,within 1.0%(electric speed regulator),within 4.5%(mechanical speed regulator)

Frequency Undulation

load from 0-100%,frequency undulation within 0.25%

No load wire volts max undulation ration\ within 1.8%

Three Phrased balanced load in the order of 5%

Effect factor of Telecom

TIF better than 50

THF to IEC60034 Part 40 better than 2%



50HZ, 1500RPM,3-PHASE,400/230V

Gensets model	Power output(KVA)		Power output (KW)		Cummins Engine Model	Leroy somer Alternator
	PRP	ESP	PRP	ESP		
M-C163	150	163	120	130	6CTA8.3G2	LSA44.2M95

(1) Available in the following voltages:220V-240V AND 380V-415V(440V)-50HZ

(2) PRP:Prime Power-Continuous duty operation,under variable load 24/24-h-10% overload permissible 1 hour/12hours.

(3) Rating Definitions (Operation at Altitude 1000m, Ambient temperature 50)Continuous Power.These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power.

Engine & Alternator

ENGINE--Industrial 4 stroke cooled diesel engine complete with air,fuel and oil filters,electric starting and charging equipment,engine protection against low water level.

ALTERNATOR--Brushless,self exciting,self regulation,sreen protected,drip proof rated in accordance with IEC60034.Voltage regulation maintained within $\pm 0.5\%$ from no load to full load.between 0.8 lagging and unity.All standard voltages available.

COOLING--Radiator and colling fan complete with protection guards,designed to cool engine at specified output in air temperatures upto 50 ,radiators suitable for higher temperatures are available.Low water level protection fitted as standard.

ELECTRICAL SYSTEM--24V upto.Axial type starter motor,battery charging alternator,high capacity lead acid battery,and battery tray mounted on the generator base frame,and heavy duty interconnecting cable with terminations.

EXHAUST SYSTEM--Heavy duty industrial exhaust silencer with flexible piping.

Technical Data Sheet

Generating sets model:

400V,50Hz,1500 rpm

Engine Model:	Cummins 6CTA8.3G2
Type	6 cylinder,4 cycle diesel
Aspiration	Turbocharged
Bore/Stroke	mm 114X1135
Compress the ratio	17.0/1
Cooling system	Water-cooled
100% Load Fuel Consumption	L/H 20
Engine Speed/Frequency	RPM/Hz 1500/50HZ
Rated Output	kw/bHP 133/181
Exhaust air flow	(m3/min) 186
Coolant Capacity	L 31
Starting System	Electric 24 volt DC
Displacement	L 8.3
Lubricant system Capacity	L 20
Battery Volatge / Capacity	24VDC
Governing Type	Electrical (GAC governor)
Exhaust Gas Temperature	640
Exhaust Gas flow	m3/min 30.84
Noise level	dBA@7m 70dBA(canopy type)

Genset Option Features

Low fuel level alarm shutdown
Automatic Fuel Filling System
Engine oil feeding and drain pump
Auto Transfer Switch(ATS)
Parallel control panels
Circuit Breaker MCCB & ACB
Remote Control Panel
weatherproof/soundproof Canopy
Trailer type Gensets

QUALITY STANDARDS

ISO9001:2000,ISO14000,ISO3046
ISO8528 BS4999
BS5514,AS1359,ICE34
CE Compliance

Gensets Dimensions & Weight

Open type:L*W*H,mm
2274×980×1472
Enclosure type:L*W*H,mm
3280×1080×1830

Alternator Technical data

Leroy somer

Bruxhless,self exciting
Class "H" insulation
Standard degree of protection is IP23
self regulating
With fan cooling
Resist Humid grease
AC excitation,roating rectification tube
Stator grease insulation covered
Rotor and exciation high polymer,Resist the corruption of oil and acid
Rotator ballance is in accordance with BS5625 standard
12.5
High-quality lubrication sealed long-time bearing
Rotor silicon steel close tight

Exciter	Brushless
Cooling Fan	Cast alloy aluminum
Bearing	Single,double shielded
Windings	100% copper
Connection Type	Reconnectable
Insulation Type	Class H
Pitch	2/3
Amortisseur Winding	Full
Voltage Regulator	AVR R250
Voltage Regulator NL-FL	$\pm 0.5\%$
Underspeed Protection	Standard
Overexcitation Protection	IP23
TIF (1960 Weightings)	<50
Exciation System	SHUNT

Control Panel -Datakom

The base mounted control panel in a vibration isolated sheet steel enclosure. The control panel is equipped as follows:

- Instruments: Analogue Voltmeter, Hours Run Meter, Water pressure Meter.
- Controls: Emergency Stop Pushbutton, Voltmeter Phase Selector Switch.
- Control module: Standard collocation is Turkey Datakom 507 Auto start with AMF.



Control module Turkey Datakom 507

Main Features:

- Δ Automatic mains failure
- Δ Engine control, Generator protection
- Δ Built in alarms and warnings
- Δ Remote Start operation available
- Δ Daily / weekly / monthly exerciser
- Δ Weekly operation schedule programs
- Δ Fuel pump control
- Δ ECU control and monitoring via J1940 CANBUS
- Δ Mains simulation
- Δ Block heater control
- Δ Field adjustable parameters
- Δ Free MS-Windows Remote monitoring
- Δ LED displays
- Δ Configurable analogue inputs
- Δ I/O expansion capability

Sound Attenuated Enclosure/Option

Robust Corrosion Resistant Construction

Black finish stainless steel lock and hinges
body made from steel components treated with polyester powder coating

Excellent Access for Maintenance

two large doors on each side
radiator fill access plate
lube oil and cooling water drains pipes to exterior of the enclosure

Security and Safety

control panel viewing window in a lockable access door
emergency stop push button (red) mounted on enclosure interior
cooling fan and battery charging alternator fully guarded
exhaust silencing system totally enclosed for operator safety



MINGPOWER reserves the right to modify the characteristics of its product at any time in order to incorporate the latest technological developments. The information contained in this document may therefore be changed without notice. For more technical data

Manufacture in China: Fujian Minghui Mech & Elec Co., Ltd.

Addr: P.O. Box: No.8 plot Gulou Park Jinshan
Industrial Zone Fuzhou, China 350008
TEL: + 86 591 83056673
Fax : + 86 591 83855582
sales@mingpowers.com
www.mingpowers.com